

*true rms, double insulation coil, smart, auto range*

# **FLEXIBLE CLAMP METER**

**Model : CMF-3200**

**ISO-9001, CE, IEC1010**

**TMI**



## **FEATURES :**

- \* Flexible clamp meter, complete set with meter
- \* Slim flexible clamp probe, easy and convenient measure the ACA up to 3000A ( auto range ).
- \* The meter also has more other features available for the ACV, DCV, Ohm, capacity, diode, continuity, measurement.
- \* Flexible probe length : 300mm ( 11.8 inch ).
- \* Flexible probe diameter : 8 mm.
- \* AC 3000 A/ 600 A, auto range.
- \* V : ACV, DCV, measurement automatically.
- \* Ohm : Ohm, Diode, Continuity, Capacitance. automatically
- \* Push button Key : Power, Hold, Select.
- \* LCD Display is 6000 counts.
- \* Auto power off.
- \* CAT III 1000V.
- \* Power supply : DC 1.5V battery ( AAA ) x 2 PC.



**Lutron**

**LUTRON ELECTRONIC**

***The Art of Measurement***



Test and Measurement Instruments C.C. [www.instrumentsgroup.co.za](http://www.instrumentsgroup.co.za) Tel: 011 683 4365 [t.m.i@iafrica.com](mailto:t.m.i@iafrica.com)

true rms, double insulation coil, smart, auto range



# FLEXIBLE CLAMP METER

Model : CMF-3200

## FEATURES

* Meet IEC 1010, CAT III 1000 V safety requirement.
* 6000 counts A/D, high resolution.
* True RMS
* Double insulation coil.
* ACA, DCV, ACV, ohms, continuity. Capacitance, Diode.
* Smart function, Auto range.
* Smart operation, Build in 3 intelligent function : " V ", " Ω ", " A " .
* " V " function can select DCV, ACV automatically with auto range.
* " Ω " function can select the Resistance , Diode, Continuity beeper, Capacitance automatically with auto range.
* " ACA " 600A " & " 3000A " automatically.
* Data hold .
* Auto shut off is available to save battery life.
* 10 M ohm impedance for voltage circuit.
* Built-in overload protection for most ranges.
* LSI circuit provides high reliability and durability.
* Uses durable, long-lasting components, enclosed in strong, light weight ABS-plastic housing.

## GENERAL SPECIFICATIONS

Display	33.5 mm x18.7 mm, LCD display.
Measurement	DCV, ACV, ACA, Resistance,Capacitance, Diode, Continuity beeper.
A/D counts no.	6000 counts.
Smart function	* " V " function can select ACV, DCV automatically with auto range. * " Ω " function can select the Resistance,Diode, Continuity beeper,Capacitance automatically with auto range. * ACA " 600A ", " 3000A " automatically with auto range.
Data hold	To freeze the display reading on the LCD display.
Power On/Off management	Auto power of or manual power off.
Selection	Smart function or auto function .
Polarity	Automatic Switching, " - " indicates negative polarity.
Sampling time	Approx. 0.5 to 1 second.
Operating Temp.	0 °C to 50 °C (32 °F to 122 °F)
Operating humidity	Max. 80% RH.
Power supply	DC 1.5 V battery ( UM-4, AAA ) x 2.
Power consumption	Approx. DC 16.1 mA.
Flexible cable length	300 mm.
Flexible Cable Diameter	8 mm.
Dimension	290 x138.3 x 26.5 mm ( 11.4x 5.4 x 1.0 inch ).
Weight	197 g/0.435 LB ( w.o battery ).
Accessories included	Operation manual..... 1 PC Test leads ( CATIII 1000 V )..... 1 pair
Optional accessory	Soft carrying case

## ELECTRICAL SPECIFICATIONS (23± 5 °C)

AC Current	* true rms
Range	600 A/3000 A
Resolution	0.1A /1 A

\* Appearance and specifications listed in this brochure are subject to change without notice.

'1511-CMF-3200

AC Current	* true rms
Accuracy	600 A Range ± ( 1% +8d ). 3000 A Range ± ( 1% +10d ).
Linearity	± 0.2% of reading value from 10% to 100% of range value.
Conductor position sensitivity	± 2% of reading value * <i>The measured conductor distance from center &gt; 25 mm (1" ) .</i>
External field influence	Increase ± 1.5% of range value max. * <i>Recommend the distance between different " Flexibel current probe " should &gt; 200 mm.</i>
Remark	* Accuracy is specified that the measured conductor's position is on the center of " Flexible current probe ". * ACA specification be tested on sine wave 50/60 Hz. * Measurement range : 0.1 A to 3000 A

DC Voltage	
Range	6 V/60 V/600 V /1000 V
Resolution	0.001V /0.01V /0.1V/1 V
Accuracy	± ( 0.8% + 5d )
Input impedance	10 M ohm.
Over load protection	± 1000 DCV, 1000 ACV

AC Voltage	* true rms
Range	6 V/60 V/600 V/1000 V
Resolution	0.001 V /0.01 V /0.1 V/1 V
Accuracy	± ( 1% + 8d ) * <i>Spec. are tested under 50/60 Hz.</i>
Input impedance	10 M ohm.
Over load protection	± 1000 DCV, 1000 ACV
Smart function test	It must be > 300 mV AC.

Diode	
Short/non conductance, good/defect test	

Capacitance	
Range	6 nF/60 nF/600 nF/6 uF/60 uF/600 uF
Resolution	0.001nF/0.01nF/0.1 nF/0.001uF/0.01uF/0.1uF
Accuracy	± ( 3 % + 10d )
Over load protection	± 30 DCV, 30 ACV.
Remark	* Discharge capacitor before testing. * Smart function must be > 0.4 nF.

OHMS	
Range	600 Ω /6 KΩ /60 KΩ /600 KΩ /6 MΩ /60 MΩ
Resolution	0.1 Ω /0.001 KΩ /0.01 KΩ /0.1 KΩ /0.001 MΩ /0.01 MΩ
Accuracy	600 ohm : ± ( 1 % + 5d ) 6K/60K/600K/6M/60M : ± ( 1.5 % + 5d )
Over load protection	± 350 DCV, 350 ACV.
Remark	60MΩ measurements must be operated in the automatic shift mode

Continuity Beeper	
Beeper will sound if measured resistance less than 20 ohm.	

